



Rotaia



Rotaia con Mantovana

MODELLO / MODEL	SLIDE 80 R	SLIDE 80
Alimentazione motore / Power supply	24 Vdc	24 Vdc
Peso max totale / Total max weight	160 Kg	160 Kg
Luce max / Max Dimension	250 cm	300 cm
Velocità / Velocity	10 cm/s	10 cm/s
Potenza motore / Absorbed power	40 W	40 W
Assorbimento medio / Average absorption	0,8 A	0,8 A
Forza / Force	80 N	80 N
Ciclo di lavoro / Duty cycle	10 cycle/hours	10 cycle/hours
Rumorosità / Noise level	50 db	50 db
Grado di protezione / Degree of protection	IP 56	IP 56
Frequenza / Frequency	433 MHz	433 MHz
Irreversibile / Irreversible	Sì / Yes	Sì / Yes
Elettroblocco / Electric lock	Sì / Yes	Sì / Yes

CODICE / CODE	MODELLO E COLORE / MODEL AND COLOUR
SL80	Motore 1/2 ante / Automation for 1/2 shutters
SL80R	Motore Radio 1/2 ante / Radio automation for 1/2 shutters
AC.K820	Kit trasmissione / Kit belt tractor
PC.R150	Rotaia anodizzata 150kg / Rail anodized 150kg
AC.KCAR	Kit carrelli / Kit truck with rollers
AC.IMPA	Kit telescopico / Kit of adjustable hardware
AC.TEL2	Radio comando / Remote control unit
AC.ELT	Elettro pistone / Solenoid to fall
AC.AL24	Alimentatore 230Vac-24Vdc
AC.AL24	Power Unit 230Vac/24Vdc